# **9** software

# Adabas SOA Gateway

**Starting and Stopping POSIX** 

Version 2012-12-17

December 2012

# Adabas SOA Gateway

This document applies to Adabas SOA Gateway Version 2012-12-17.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2006-2012 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, United States of America, and/or their licensors.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at http://documentation.softwareag.com/legal/.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at http://documentation.softwareag.com/legal/ and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". This document is part of the product documentation, located at http://documentation.softwareag.com/legal/ and/or in the root installation directory of the licensed product(s).

Document ID: APS-POSIX-TBD-20121217

## **Table of Contents**

1 Starting and Stopping POSIX	
POSIX Server Initialization	2
POSIX Server Termination	

# 1 Starting and Stopping POSIX

POSIX Server Initialization	2
POSIX Server Termination	3

This chapter covers the following topics:

- POSIX Server Initialization
- POSIX Server Termination

## **POSIX Server Initialization**

#### In Batch

For OS/390 or MVS/ESA batch, any POSIX server-enabled program may be

- started by first invoking the POSIX server kernel module PABNKERN as shown in the sample job PJBNRUN.
- invoked directly using the EXEC PGM= statement. The POSIX server is then initialized the first time a POSIX server request is issued.

For VSE/ESA batch, any POSIX server-enabled program may be

- started by first invoking the POSIX server kernel module PAVNKERN as shown in the sample job PJBNRUN.J.
- invoked directly using the `EXEC pgm' statement. The POSIX server is then initialized the first time a POSIX server request is issued.

For batch in other environments, see the documentation for the particular Software AG application product that uses SMARTS.

### In CICS

The POSIX environment is initialized by the PACNKERN program, which can be invoked by a CICS transaction (SMGO) or by placing the program PACNSMGO in the CICS PLTPI table.

#### In the SMARTS Server Environment

The POSIX server is normally initialized by specifying a SMARTS statement such as

```
SERVER=(Posix,PAENKERN)
```

- where

Posix	is the name of the SERVER. The name of the server may be any name valid for the SERVER	
	statement.	
PAENKERN	is the name of the POSIX server kernel module. The POSIX server module must always be	
	specified as PAENKERN.	

If inactive for any reason, the server may also be started using the SMARTS operator command

#### SERV,INIT,Posix,PAENKERN

- where the meaning of the parameters is the same as previously outlined for the SERVER statement.

#### If the POSIX Server Initialization Fails

If the POSIX server initialization fails, the POSIX server configuration is probably invalid:

- Check for messages during the POSIX server initialization process that may identify the problem.
- Check in particular for sockets errors that occur if the incorrect TCP/IP stack is identified to the POSIX server and/or the incorrect address space or subsystem name is supplied for the appropriate TCP/IP stack.

## **POSIX Server Termination**

#### In Batch

For OS/390 or MVS/ESA batch, if the POSIX server was invoked using the PABNKERN module, the POSIX server-enabled program terminates first, giving control to the routine that terminates the POSIX server subsystem.

For VSE/ESA batch, if the POSIX server was invoked using the PAVNKERN module, the POSIX server-enabled program terminates first, giving control to the routine that terminates the POSIX server subsystem.

If the POSIX server was initialized implicitly by a POSIX server-enabled program, the initialization process ensures that a batch-specific routine receives control after the POSIX server-enabled program is terminated in order to terminate the POSIX server and return control to the operating system.

For batch in other environments, see the documentation for the particular Software AG application product that uses SMARTS.

### In CICS

The POSIX environment is terminated by the PACNKERX program, which can be invoked by a CICS transaction (SMEX) or by placing it in the CICS PLTSD table.

### In the SMARTS Server Environment

The POSIX server is terminated automatically when the SMARTS address space is terminated; however, it is also possible to cycle the server without bringing the address space down by issuing the SMARTS operator command

#### SERV,TERM,Posix

- where 'Posix' is the name given to the server at startup.

#### Notes:

- 1. When this command is issued, current users of the POSIX server are either canceled or ignored. Attached processes are canceled while terminal users are ignored causing their entire session to be terminated. Consider using the POSIX server operator command QUIESCE for a period prior to actual termination.
- 2. The POSIX server does not terminate until all users of its services have terminated. The user should issue the termination command again once it appears that all POSIX users have terminated. It is possible to FORCE it down using the POSIX server operator command FORCE ; however, Software AG does not recommend this as the results are unpredictable.
- 3. The POSIX server does not terminate if there are dependent services still active. For example, if HTTP servers are still active, the POSIX server will not terminate until these are terminated. Again, the POSIX server operator command FORCE may be used, although Software AG does not recommend it.